



<p>[1-1]</p> <p>PCB 1.6 mm thick</p> <p>DUMMY-CHIP 12.7mm SQ 1.7mm thick</p> <p>HEATSINK QTUM45-25B 37.0g</p> <p>SPRING S001YZ4J TSPH-0.8-3.4</p> <p>ANCHOR ANCR-11</p> <p>TIM YG6260</p> <p>TOTAL FORCE 2.1 kgf (20.9N) 18.8PSI</p>	<p>[1-3]</p> <p>PCB 1.6 mm thick</p> <p>DUMMY-CHIP 12.7mm SQ 1.7mm thick</p> <p>HEATSINK QTLM50-30B 39.9g</p> <p>SPRING S001YZ4J TSPH-0.8-3.4</p> <p>ANCHOR ANCR-11</p> <p>TIM YG6260</p> <p>TOTAL FORCE 2.1 kgf (20.9N) 18.8PSI</p>	<p>[2-1]</p> <p>PCB 1.6 mm thick</p> <p>DUMMY-CHIP 25.0mm SQ 3.6mm thick</p> <p>HEATSINK UBP80-25B 150.0g</p> <p>PUSH-PIN PIP3.175x18.8</p> <p>SPRING S001YJ02</p> <p>TIM YG6260</p> <p>TOTAL FORCE 8.2 kgf (80.8N) 18.7PSI</p>
<p>[1-2]</p> <p>PCB 1.6 mm thick</p> <p>DUMMY-CHIP 12.7mm SQ 1.7mm thick</p> <p>HEATSINK QTLM60-30B 57.3g</p> <p>SPRING S001YZ4M TSPH-1.0-3.4</p> <p>ANCHOR ANCR-12</p> <p>TIM YG6260</p> <p>TOTAL FORCE 4.2 kgf (41.6N) 37.4PSI</p>	<p>[1-4]</p> <p>PCB 1.6 mm thick</p> <p>DUMMY-CHIP 12.7mm SQ 1.7mm thick</p> <p>HEATSINK QTUM60-25B 64.3g</p> <p>SPRING S001YZ4M SPH-1.0-3.4</p> <p>ANCHOR ANCR-12</p> <p>TIM YG6260</p> <p>TOTAL FORCE 4.2 kgf (41.6N) 37.4PSI</p>	<p>[2-2]</p> <p>PCB 1.6 mm thick</p> <p>DUMMY-CHIP 25.0mm SQ 3.6mm thick</p> <p>HEATSINK UBP90-15B 134.0g</p> <p>PUSH-PIN PIP3.175x14.3</p> <p>SPRING S001YJ0G</p> <p>TIM YG6260</p> <p>TOTAL FORCE 6.8 kgf (66.5N) 15.4PSI</p>
<p>[4-1]</p> <p>PCB 1.6 mm thick</p> <p>DUMMY-CHIP 25.0mm SQ 2.5mm thick</p> <p>HEATSINK FSP50-25M45 (FAN) 69.0g</p> <p>PUSH-PIN PIP3.175x14.3</p> <p>SPRING S001YJ1F</p> <p>TIM YG6260</p> <p>TOTAL FORCE 3.9 kgf (37.9N) 8.8 PSI</p>	<p>[3-1-1]</p> <p>PCB 1.6 mm thick</p> <p>DUMMY-CHIP 12.7mm SQ 2.5mm thick</p> <p>HEATSINK UB19-25B 6.0g</p> <p>QSZ CLIP QSZ24x24R (φ1.0)</p> <p>ANCHOR ANCR-11</p> <p>TIM YG6260</p> <p>TOTAL FORCE 1.2 kgf (11.8N) 10.6PSI</p>	<p>[2-3]</p> <p>PCB 1.6 mm thick</p> <p>DUMMY-CHIP 25.0mm SQ 3.6mm thick</p> <p>HEATSINK UBP100-25B 264.0g</p> <p>PUSH-PIN PIP3.175x20.3</p> <p>SPRING S001YJ2T + 0.5mm thick washer</p> <p>TIM YG6260</p> <p>TOTAL FORCE 14.3 kgf (140.6N) 32.6PSI</p>
	<p>[3-1-2]</p> <p>PCB 1.6 mm thick</p> <p>DUMMY-CHIP 12.7mm SQ 2.5mm thick</p> <p>HEATSINK UB25-25B 12.0g</p> <p>QSZ CLIP QSZ29x29 (φ1.2)</p> <p>ANCHOR ANCR-11</p> <p>TIM YG6260</p> <p>TOTAL FORCE 1.65kgf (16.2N) 14.5PSI</p>	